

# RIG-20



# Specifications

## Rig HorsePower

- 2000hp

## Mast

- K type, 45.5 m(149.3 ft)

## Traveling Block

- YC-450 Conforms to API Specs

## Drawworks

- DC motor drive
- to be equipped with Crown-O- Matic switch.

## Mud pumps

- 1,176 KW (1,600 HP) × 2

## Mud Processing

- TBA

## Top Drive

- Canrig 8050AC

## Swivel

- 3 x 5000 psi

## Rotary Table

- Ea Model : ZP-375

## Drill Pipe

- 5" x 8576 mtr 19.5 ppf
- 5" x 18 joints 4 1/2 IF 49.3ppf

## Drill Collar

- 12-2-1 6 3/4
- 12-2-2 6 1/2"
- 12-2-3 7 3/4"
- 12-2-4 9 1/2"

## BOP

- 13- 5/8" 10,000psi

## Choke Manifold

- 3-1/6" 10M wp

## Standpipe Manifold

- 5 x 5,000psi

## Camp Facility

- Bed Facility
- Galley, Mess Room, Recreation Room
- Store, Hospital

## Rig Site Facility

- Toolpusher & Company Man Office & Room
- Change Room, Service Company Office.

## Depth Rating

- 6,000 meters